

DESCRIPTION

PETROMIN SUPER SYNTHETIC GF5 is a high performance lubricant using fully synthetic technology, specially developed for Gasoline and Diesel car engines, meeting and complying with the requirements of the latest direct injection engines and conventional engines as well.

APPLICATION

- Recommended for all Gasoline and Diesel engines in cars and light industrial vehicles.
- All turbocharged and multi-valved engines.
- Suitable for most severe operating conditions, on highways, dense city traffic & in extreme weather conditions.
- Suitable & exceeds the performance requirements of most European, Japanese and American car manufacturers.

BENEFITS

- Ensuring sustainable high performance, thus meeting the needs of the engines in term of extended and better oil drain intervals; consequently doubling the oil drain mileage.
- Guaranteeing high & constant quality by excellent detergent properties giving greater engine cleanliness for enhanced performance.
- High Viscosity Index resulting in stable viscosity during operation.
- Fully miscible with other engine oils.
- Less oil top-up
- Superior antiwear properties protecting the engine's most sensitive parts.
- Easy cold start and ideal lubrication at elevated temperature, ensures low oil consumption and cold start protection against wear.

PERFORMANCE LEVEL

API.....	SN/ILSAC GF-5
Daimler Chrysler.....	MB 229.31
Volkswagen	502.00/505.00
BMW	Long-life-04
HONDA	HYUNDAI
NISSAN	KIA
TOYOTA	SUZUKI

PRODUCT CHARACTERISTICS*

PROPERTIES	UNITS	VALUE		TEST METHOD
SAE Grade	-	5W-30	10W-30	-
Specific Gravity @ 15 °C	-	0.851	0.852	ASTM D-4052
Viscosity	@ 40 °C mm ² /s	71.9	72.22	ASTM D-445
	@ 100 °C mm ² /s	11.9	11.84	ASTM D-445
Viscosity Index	-	162	160	ASTM D-2270
Flash Point, COC	°C	222	226	ASTM D-92
Pour Point	°C	-39	-36	ASTM D-97
Base Number	mg KOH/g	7.0	7.0	ASTM D-2896
Product Code	-	1180	2940	

*The information and figures given here are typical of current production and conform to specifications, minor variations may occur.